



Manufacturer of PCB Terminal Blocks, Fuse Holders, Barrier Terminals, & Switches

RM4FUL



Vital make fuse terminal model RM4FU is used in wiring systems where fuse protection is required. RM4FU model is suitable for 5 x 20 mm or 5 x 25 mm glass cartridge fuse.

PRODUCT INFORMATION :

Product name:	RM4FUL (6-60V), RM4FUL (110-240V)	
Connection method:	Feed through, screw connection type.	
Rating:	6.3 A / 800 V / 4 sq mm / 0.5 Nm	
Led ratings:	Suitable for 6-60V or 110-204V	
HSN number:	85369090	
Standard packing quantity:	25 NOS	
Country of origin:	INDIA	
Screw thread:	M3	

TECHNICAL DATA:

DIMENSIONS

Height:	50 mm	2.23 inch	
Width:	57 mm	2.25 inch	
Thickness:	8 mm	0.31 inch	
Screw size:	M3		
Standard wire size:	4 sq mm		
Channel size:	DRC15, DRC35		

Off/Works: 830/2, GIDC Estate, Makarpura, Vadodara- 390010

I

Office: +91 - 9227979802 / 4

Sales: +91-9227979801

Email: sales@vitalelectrocomp.com

Web: www.vitalelectrocomp.com

Note: Technical specifications are subject to change without prior notice

Copyright© 2024 by Vital Electrocomp. All Rights Reserved

*Continue





Manufacturer of PCB Terminal Blocks, Fuse Holders, Barrier Terminals, & Switches

RM4FUL

MATERIAL

Body material:	POLYAMIDE 66	
Standard colour:	Grey	
Colour options:	Red, Yellow, Blue, Black, Green, Charcoal	

IEC RATING

	Connection in acc with standard	IEC 60947-7-1, IEC 60947-7-3	
Nominal voltage		800 V	
	Nominal current	6.3 A	
	Nominal cross section	4 sq mm	
	Rated surge voltage:	8 kV	
	Degree of pollution:	3	

*Accessories Available for RM4FU terminal: Markers – plain and printed

Off/Works: 830/2, GIDC Estate, Makarpura, Vadodara- 390010				
Office: +91 - 9227979802 / 4	Ι	Sales: +91-9227979801		
Email: sales@vitalelectrocomp.com	Ι	Web: www.vitalelectrocomp.com		
Note: Technical specifications are subject to change without prior notice	Ι	Copyright© 2024 by Vital Electrocomp. All Rights Reserved		